

Examples from our product range

			GODIPLAST PVC-P GG76-16	GODIPLAST PVC-P GI58-58	GODIPLAST PVC-P GF78-84	GODIPLAST PVC-P GX89-09	GODIPLAST PVC-P GT69-85	GODIPLAST PVC-P GR65-85	GODIPLAST PVC-P GW69-58	GODIPLAST PVC-P GM56-07
			black, Injection moulding, skin tolerant, easy flowing	clear, Injection moulding, medical disposables, suitable for ethylene oxide sterilisation	grey, Injection moulding, high tensil strength, Joints	black, Injection moulding, easy flowing, Plugs	black 9004, Injection moulding, high tensil strength, medical disposables, suitable for ethylene oxide	black, Injection moulding, softest setting, skin tolerant	grey, Extrusion, high tensil strength,	klar, Injection moulding, soft setting, Joints
Density	DIN 53479	g/cm³	1,39	1,20	1,35	1,46	1,27	1,30	1,31	1,19
Hardness (Shore-A)	DIN 53505	°	62	74	77	85	93	45	92	55
Tensile strength	DIN 53504	N/mm²	> 5	> 9,5	> 12	> 8	> 15	> 2,5	> 18	> 5
Elongation at break	DIN 53504	%	> 250	> 300	> 230	> 100	> 200	> 300	> 120	> 300